KIAPS Next Generation Global Model

Young C. Kwon, Song-You Hong

Korea Institute of Atmospheric Prediction Systems (KIAPS)

Contents

- Overview of KIAPS
- Dynamical core
- Physics
- Data assimilation
- System optimization
- Verification

Overview of KIAPS

☐ Purpose: Developing a next generation global

operational modeling for KMA

☐ Project period: 2011~2019(toal 9 years)


□ Total Budget: \$95 million

2015 budget -\$8.5 million

☐ KIAPS is founded at Feb. 15th 2011


o organization: 2 divisions, 6 teams, 1 office

Man power: 55/58



Total	Director	Research Staff			Administrative staff		
		Principal Researcher	Senior Researcher	Researcher	Principal Staff	Senior Staff	Staff
55	1	12	25	11		3	3

Three-stage development plan of KIAPS Global Model




Development of dynamic core

Dynamic core of KIM (KIAPS Integrated Model)

	KIM-SH (High Order Method Modeling Environment model; NCAR's CAM-SE)	KIM-SW (Kiaps Integrated Model – Spectral element method, WRF-Type)		
Spherical grid	Cubed-sphere (Equi-angular gnomonic projection)			
Horizontal approximation	Spectral Element			
Vertical approximation	Finite Element	Finite Difference		
Temporal approximation	• I Leantrod Tirst-Order dile to I ' ' '			
Equation	Hydrostatic (Full variables)	Non-hydrostatic) (Perturbation variables)		
Explicit spatial diffusion				

KIM (KIAPS Integrated Model)



Hydrostatic/Non-hydrostatic system with spectral element method over cubed sphere grid (as in CAM-SE)


Advantage:

- 1. Avoid pole singularity
- 2. Better scalability

Disadvantage

- 1. Grid imprinting
- 2. Non-conservative

Rotation of Cubed Sphere



Development of Non-hydrostatic Dyn.

- KIM-SW (based on WRF governing equations)
 - Cubed sphere, horizontal: Spectral element, vertical: FD, terrain-following
 - Flux-type compressible governing equations in perturbation form with prognostic variables
 - Time-split time integration: Slow mode → third-order Runge-Kutta

Horizontal sound wave and gravity wave → Forward-Backward vertical sound wave and buoyancy → implicit


2D (x-z) Slice 3D 3D **3D** 2D Shallow Aqua-Planet Dry Dry **Atmospheric Experiments** Water Test **Dynamical** Dynamical **Model test Core Tests Core Tests** (APE) 1. Advection of 1. Steady-sate 1. Control APE 1. the 5-case for a 1. Linear hydrostatic 2. Baroclinic wave cosine bell mountain wave 2. 3KW1 APE severe weather 2. Steady state 2. Simulations The 3. 3D Rossby-Haurwaitz wave 3. Translating low Schar-type mtn. 4. Mountain-induced Rossby wave 4. Zonal flow over an 3. Density current 5. Pure gravity wave isolated mountain 6. DCMIP pure advection test 4. Inertial-gravity wave 5. Rossby-Haurwitz 5. Rising thermal bubble 7. DCMIP Mountain-wave over a Schar-type 2015 8. Held-Suarez (Choi et al., 2014) wave

(Choi and Hong, 2015)

Development of Non-hydrostatic Dyn.

140E

Longitude



Longitude

Development of Non-hydrostatic Dyn.


Heavy rainfall case over the Korea peninsula: 24hr accumulated precipitation (24-48hr, ~25km) **TMPA** 24-hour accumulated precipitation(mm) **AWS** 60S ne120np4 201107 Precip. Core — Precip. Core 125E 30E 60E 90E 120E 150E 180 150W 120W 90W 60W 30W — Korea **— —** Когеа 80 KIM-SW 24-hour accumulated precipitation(mm) Rainfall 30S 20 125E 60E 90E 120E 150E 180 150W 120W 90W 60W 30W . 26jul 27jul 28jul 29jul 30jul 31jul 1Aug 2Aug 3Aug 4Aug


Time (UTC)


Development of Advanced Dynamical Core

■ Vertical finite difference → vertical finite element

- More accurate than VFD
- The level of computational mode may be reduced








12

Exploring variable resolution KIM (e.g. 3km around Korea)




Development of physics

Physics upgrades (1.0: 201402 2.2: 201601 2.4:20160701)


	KIM1.0 (1단계)	KIM2.2 (2016. 1. 1.)	KIM2.4 (2016. 7. 1., plan)		
Radiation	RRTMG	RRTMG+new aerosol climatology/surfa ce albedo and emissivity	RRTMG <u>+new aerosol climatology/surface</u> <u>albedo and emissivity+code dean-up+new</u> <u>snow albedo+cloud overlaping</u>		
Convection	deep: SAS (Han and Pan, 201 1) shallow: Han and Pan (2011)	deep: SAS + scale-aware + autoconversi on shallow: Hong et al. (2013)+eddy diffusi vity profile	deep: SAS + scale-aware + autoconversion + diurnal variation shallow: Hong et al. (2013)+eddy diffusivity pro file 개선		
Microphysics	WSM6 (Hong and Lim, 2006) WSM5 (Hong et al. 2004) + effective ius		WSM5 (Hong et al. 2004) + effective radius+Pa rtial cloudiness		
Cloudiness	Wilson and Gregory (2003)	prognostic cloudiness (Park et al., 2016) + CPS cloud fraction effect	prognostic cloudiness (Park et al., 2016) + CPS c loud fraction 산출방법개선		
Orographic GWD	McFarlane (1987)	Kim-Arakawa (Hong et al. 2008) + flow- blocking drag + orographic anisotropy	Kim-Arakawa 방안 (Hong et al. 2008) + flow-blocking drag + orographic anisotropy+improve tress		
Non-orographic GWD	Warner and McIntyre (2001)	Chun and Baik (1998) (Jeon et al. 2010)	<u>Chun and Baik (1998) 기반대류중력파 방안</u> (Jeon et al. 2010) + non-stationary GWD		
LSM	Noah v2.5 LSM	Noah v3.0 LSM+ 3-layer sea-ice model + MOSAIC	Noah v3.0 지면모델 + 3-layer sea-ice model + MOSAIC+ verification		
PBL	YSU	YSU + top-down mixing	YSU + top-down mixing+scale -aware		

GWDO

Advanced Physics



Heavy snowfall event (18UTC03-06UTC04 Jan. 2010)



Weakened low-level wind speed →reduced heat fluxes → Improved snowfall overestimation over Korea

Prognostic Cloudiness

Advanced Physics

Diagnostic cloud fraction (Xu and Randall, 1996)

$$C_{s} = RH^{P} \left[1 - \exp\left(-\alpha_{0} \overline{q}_{I} / \left[(1 - RH) q^{*} \right]^{r} \right) \right]$$


Prognostic cloud fraction (Tiedtke, 1993)

$$\frac{\partial a}{\partial t} = A(a) + S(a)_{CV} + S(a)_{BL} + S(a)_{C} - D(a)$$


Improvement of prognostic cloud fraction (PROGC)

$$C_{Lx} = \frac{1}{50} \left\{ 5.77 \left(100 - L_x \right) q_{c,Lx}^{1.07} + 4.82 \left(L_x - 50 \right) q_{c,Lx}^{0.94} \right\}$$


Relation between cloud water and cloud fraction by cumulus convection



Improvement of cloud fraction via PROGC



Improvement of NWP performance via PROGC



Park et al. (2016)

☐ The grid-size dependency is considered (scale-aware scheme)

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$
where
$$\sigma_{\text{con}} = \frac{\tan(0.4\pi)}{\Delta x_{5\text{km}} - \Delta x_{1\text{km}}}$$
Adapted from Hong and Pan (1998, MWR)
$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \right\}$$

$$\sigma = 1 - \frac{1}{\pi} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}} \left(\Delta x - \Delta x_{5\text{km}} \right) \right] + \frac{\pi}{2} \left\{ \tan^{-1} \left[\sigma_{\text{con}}$$


- Cloud-base mass flux $[\propto (1 \sigma)^2]$
- Convective Inhibition (∝ (1-σ))
- Moisture detrained to grid scale (∝ σ)

Convective strength is negatively proportional to convective fractional area (CFA)

Convection trigger is negatively proportional to CFA


Convective detrainment of hydrometeor is positively proportional to CFA


Submitted to MWR (Kwon and Hong)



Advanced Physics


Upgrade in Noah LSM







Use of high-resolution surface data

Variables	Data		
Land use	1-km modified IGBP (MODIS)		
Soil texture	1-km STATSGO/FAO		
surface albedo	0.05° MODIS MOD43C surface albedo		
snow albedo	0.05° maximum albedo for snow-covered land		
lea area index	0.083° 30+ year climatology (LAI3G)		
displacement height	0.083° canopy height (NASA) in preparation		



Parameterization of land-surface heterogeneity





Development Data Assimilation Systems

KPOP (KIAPS Package for observation processing)


Observation data preprocessing and data assimilation system-I

Incoming obs. data monitoring system and advanced quality control method

- AMSU-A: Bias correction coeff. Improve thinning method
- GPS-RO: Add geopotential height correction and vertical thinning method
- IASI: Build routines of removing cloud effect and iterative method for BC coeff.


At the end of 2016, almost all the satellite data will be processed via KPOP

- KPOP: Construct the real-time incoming data monitoring system



Left: Original thinning method Right: Revised thinning method

- more data and smaller standard deviation



Observation data monitoring system


Observation data preprocessing and data assimilation system-II


Development of 3DVAR data assimilation system for KIM

- 3DVAR system assimilating realtime observation data
 - The observation data for KIM 3DVAR system so far

Sonde, Surface, Aircraft, AMSU-A, GPO-RO, CrIS, ATMS, AMV, IASI

- Continuing improvement of the KIAPS 3DVAR system
 - Improving computational efficiency by spectral transform algorithm
 - Improving 3DVAR performance with better back ground error covariance






Song and Kwon (2014)

RMS difference between KIM 3DVAR and UM analysis data (left: Psfc, right: theta)

Semi-Real time Cycle

- Development of 3DVAR system for hydrostatic/non-hydrostatic model
 - Modification to fit KIM-SW (non-hydrostatic model)
- Flow chart of cycling system (Warm cycle)




Observation data preprocessing and data assimilation system-III

Development of LETKF-KIM ensemble DA system


- Assimilating real observation data after idealized tests
- Improvement of additive/multiplicative inflation to enhance the performance
 - The observation data assimilated so far

Sonde, Surface, AMSU-A, GPO-RO




RMS difference of 925 hPa zonal winds compare to ERA-Interim data

Observation data



The difference of obs. data assimilated KIM (v2.2-v2.1, positive means more data for v2.2)



System Optimization

Software Framework

Computational efficiency

- Change Entire → Unique :

IO Improvement x2

Model wallclock

- Apply the **PNetCDF**:


x25


x2

x108

~ x10

- Apply the **IO decomposition**:





- KIM Profiling (v0.26.04)
- Model wallclock time
- 10 day forecasts
- $\triangle t = 30, 15 \text{ sec}$

	ne60 (50 km)		ne120 (25 km)	
core	2400	5400	2400	5400
SH + GPPACK(3.3)	1:09	0:38	8:12	3:57
SW + GPPACK(3.3)	1:35	0:53	11:19	5:27


Software Framework

Optimization in Parallelization

Install 3DVAR in the Framework

Optimization

- Rearrange the 3D arrays in AdjSpecToCtrl routine
- Remove the reproducible-sum routine



Remapping Tool Package


V-GECoRe

- Geometrically Exact conservative remapping with Voronoi diagram

Lagrange interpolation

- 3rd-order interp. in a element, the most effective for cubed-sphere


- Bilinear interpolation
- Nearest





Job scripts

Cylc scheduler

- A meta scheduler to control the complex tasks efficiently
- Possibility of setup, modification and monitoring user-friendly







Verification

Verification

Testbeds

Model

Resolution

Testbeds

KIM (KIAPS Integrated Model system) **reference models** (GRIMs, WRF)

100 km (~T126/NE30) to 25 km (~T510/NE120) 50 levels, top ~ 0.3 hPa

High-impact weather forecast

- Heavy-rainfall event
- Heavy-snowfall event
- Migratory cyclone event
- Typhoon Bolaven and Tembin
- Typhoon Sanba

Seasonal simulation

- 2013 JJA, 2013-2014 DJF
- T126I 28
- 5 ensemble members

Medium-range forecast (10-day forecast)

- cold start for July 2013, February 2014


Semi-real-time

- warm start since 1 July 2015

: v2.2


HGT: AC

20130701-31 (NE60, 240hrs)




20130701-31 (NE60, 240hrs)







V2.1



강수전반 감소, ETS 증가




3-day average of 24-h accumulated precipitation



3-day average of 24-h accumulated precipitation


Verification results of semi-real run (2016. 2)

Anomaly Correlation of geopotential height




검증스코어 모니터링: 일별






Verification for rain (CPC)




월별 준실시간 검증 스코어

북반구 500 hPa GPH AC




북반구 500 hPa GPH RMSE



KIM Semi-real-time

2015.7.13.00 UTC(+120hr fcst)



Shading: 6hr Accumulated Precipitation (mm) Contour: Mean Sea Level Pressure (hPa)

2016 Plan

	2.2 (JAN 2016)	2.3 (APR 2016)	2.4 (JUL 2016)	2.5 (OCT 2016)
Dynamic		High order diffusionHybrid verticalcoordinate	complete standard dynamic coreprepare dx=10km dynamic core	· start dx=10km dynamic core
Physics	climatology data for physics packageUpdate physics package	Minor bug fix of v2.2Complete standard physics package	 develop advanced physics package 	 Complete advanced physics package
Data Assimilation (3DVAR / LETKF)	· IASI, AMV (85 %)	· ATMS (temperature), CrIS (90 %)	· ATMS (moisture), MHS, CSR (95 %)	· ScatWind, SSMIS (100 %)
	· Improve background error covariance	· High analysis resolution (50 km)	· 4D Hybrid EnVAR	· High analysis resolution (25km)
	· Conventional, AMSU-A, GPS-RO (80 %)	· Conventional, AMSU-A, GPS-RO, AMV (85 %)	· IASI (90 %)	· CrIS, MHS (95 %)
	· Coupled with KIM v2.1	· Initial semi-real time version	· Improve ESV	· Optimize ESV
System	Update surface cyclingUpdate ancillary data	Rotate cubed sphere gridSpectral filter topography	Update KIM frameworkCode clean up and standardization	Develop KIM-APIDevelop KIM coupler
Verification	Verification of physics packageVerification of semi-real time KIM	Standard verification system (KAT-STAT)Verification of semi-real time KIM	Standard visualization tools (KAT-PLOT)Verification of semi-real time KIM	· Verification of semi-real time KIM

^{*} ESV: Ensemble Singular Vector * API: Application Programming Interface